



DATASHEET | OCTOBER 2022

Transforming Navigation



Applications

Artillery Survey to Mark:

- Survey Control Point (SCP) Position; Used to Initialize Weapon Systems
- Orienting Line (OL) Position and Azimuth; Used to Initialize and Align Artillery Assets

Key Performance Features

- High-Precision Common Survey Enables Efficient Mass Fires
- Common Architecture and Components (MLRS, HIMARS, Firefinder, Paladin and Long-Range Air Surveillance Radar)
- Navigation Aids (compass rose and digital maps)
- In-Vehicle and Offset Survey
- Combat-Proven
- Embedded Built-In Test (BIT)
- High-Reliability MTBF, Low Mean Time to Repair (MTTR)
- No Periodic Calibration Required

Inertial Surveying System

When You Need Precision, You Need IPADS

EMCORE's Improved Position and Azimuth Determining System (IPADS) is an inertial surveying system developed to meet today's demanding U.S. Army and Marine Corps survey needs. Survey operations functionality, navigational accuracy, transportability, survivability and affordability requirements drove the system design.

EMCORE's IPADS provides significant enhancements for today's Army and Marine Corps survey teams. While meeting PADS accuracy and environmental requirements, IPADS offers a proven, reliable, lightweight, off-the-shelf solution developed around four main components.

- Compact Position/Navigation Unit (CPNU)
- Control and Display Unit (CDU)
- Battery and Charger Unit (BCU)
- Porro Prism Assembly (PPA)

All components are housed in a robust frame that allows for easy component access and stability, while facilitating a ready two-person live transfer between vehicles.



Use of U.S. DoD visual information does not imply or constitute DoD endorsement.

IPADS

Improved Position and Azimuth Determining System

Transforming Navigation

Specifications

| Performance | |
|----------------------------|---|
| 4th-Order Accuracy | |
| Orienting Line Azimuth | 0.4 mil PE, (Probable Error), 0° to 65° N/S latitude 0.6 mil PE, 65° to 75° N/S latitude |
| Horizontal | 4 m CEP (Circular Error Probable) |
| Vertical | 2 m PE 5-min. ZUPT (Zero Velocity Update) Within 75 km radius of update point |
| 5th-Order Accuracy | |
| Orienting Line Azimuth | 0.4 mil PE, 0° to 65° N/S latitude 0.6 mil PE, 65° to 75° N/S latitude |
| Horizontal | 7 m CEP |
| Vertical | 3 m PE 10-min. ZUPT Within 75 km radius of update point |
| Initialization Time | |
| Static Align | 10 min. 0° to 65° N/S latitude 20 min., 65° to 75° N/S latitude |
| Hot Start Align | 5 min., 0° to 65° N/S latitude 10 min., 65° to 75° N/S latitude |

| Characteristics | |
|-----------------|---|
| Weight | 135 lb., 61 kg (Standard configuration) 66 lb., 30 kg (Optional configuration using DRU-H-R, smaller/lighter CDU, and Li-Ion Batteries) |
| Dimensions | 24.75 in. L x 15.75 in. W x 16.125 in. H (Standard configuration) 62.87 cm L x 40.01 cm W x 40.96 cm H 16.9 in. L x 8.9 in. W x 10.8 in. H (Optional configuration using DRU-H-R, smaller/lighter CDU, and Li-Ion Batteries) 43.0 cm L x 22.5 cm W x 27.5 cm H |
| Power | Steady-State Voltage Options |
| Interfaces | - One 10/100-BaseT Ethernet (Reprogramming port) - One optional/unused RS-232 port - One optional/unused RS-422 port - Six optional/unused USB 2.0 ports |
| Environments | - Nuclear, Biological & Chemical (NBC) survivability - EMI/EMC-compliant (MIL-STD-461E/464A) - MIL-STD-810F-compliant - MIL-STD-1275D power input |

Compact Position/Navigation Unit (CPNU)

The CPNU, a three-axis strap-down inertial navigation system of ring laser gyros and high-grade accelerometers, is the core component of IPADS. It is the compact version of our proven navigation system used on the Multiple Launch Rocket System (MLRS) and High-Mobility Artillery Rocket System (HIMARS) programs.

Control And Display Unit (CDU)

The CDU is a ruggedized tablet computer featuring an Intel Dual Core i7 @ 1.7 GHz, Windows® 10, 16 GB Main RAM, Two 480 GB Solid-State Drives (SSD), and a 10.4- inch XGA touch-screen color display.

Porro Prism Assembly (PPA)

The PPA in conjunction with customer-supplied Theodolite, provides 24-meter offset survey capability. This allows surveying locations that are inaccessible by vehicle. Offset distance may be extended using optional accessories such as a handheld laser rangefinder mounted on existing manual Theodolite or using automated total stations.

Battery And Charger Unit (BCU)

The BCU uses a standard U.S. Army NSN 6130-01- 493-6643 Sealed-Lead Acid (SLA) battery. The BCU is based on the ABPAC.DC/ BT-TR-1 Transceiver Power Unit (TPU) that is currently fielded by the U.S. military. The unit allows for worldwide input of 9 to 36 VDC / 85 to 270 VAC, 47 to 440 Hz, single-phase power inputs and provides power and charge status indicators.

Notes

This information has been released into the public domain in accordance with the International Traffic in Arms Regulation (ITAR) 22 CFR 120.11(a)(7).

For More Information

+1 866.234.4976 | navigation-sales@emcore.com | emcore.com/nav

EMCORE Corporation

2015 Chestnut Street
Alhambra, CA 91803 USA

P +1 626.293.3700

F +1 626.293.3429

emcore®

ISO9001
CERTIFIED

